



### Dimensions

TYPE	A	A'	E	F	G	H
T26 in.	.079	.083 max.	.236 max.	.197 min.	.028 ± .008	.011 ± .002
T26 mm	(2.0)	(2.1 max.)	(6.0 max.)	(5.0 min.)	(0.7 ± 0.2)	(ø0.28 ± 0.05)
T38 In.	.118	.122 max.	.323 max.	.394 ± .039	.043 ± .008	.014 ± .003
T38 mm	(3.0)	(3.1 max.)	(8.2 max.)	(10 ± 1)	(1.1 ± 0.2)	(ø0.35 ± 0.07)
T3A in.	.118	.122 max.	.394 max.	.394 ± .039	.043 ± .008	.014 ± .003
T3A mm	(3.0)	(3.1 max.)	(10.0 max.)	(10 ± 1)	(1.1 ± 0.2)	(ø0.35 ± 0.07)



**TELLURIAN®**  
TECHNOLOGIES, INC.

1801 Hicks Road, Ste. B • Rolling Meadows, IL 60008

Tel: 847-934-4141 • Fax: 847-934-4175 • info@telluriantech.com

UNLESS OTHER WISE SPECIFIED,  
DIMENSIONS ARE IN INCHES (MM).  
DO NOT SCALE

DRAWN BY	<b>A</b>
CHKD BY	
APPD BY	
DATE: 12/01/98	

SIZE	<b>A</b>
SCALE:	

PART NAME Crystal: Tuning Fork Thru-Hole Package	
PRODUCT FEATURES Resistance welded package	
CUSTOMER	
DRAWING NO. T26, T38, T3A	REV